


TRUAX SEVEN DEPARTURE


AL-198 (FAA)


WILLIAM P HOBBY (HOU)
HOUSTON, TEXAS


D-ATIS
124.6
CLNC DEL
125.45
CPDLC
GND CON
121.9
HOBBY TOWER
118.7 256.9
HOUSTON DEP CON
127.125 269.075

**TOP ALTITUDE:
16000**

HOBBY
117.1 HUB 
Chan 118

EAGLE LAKE
116.4 ELA 
Chan 111

SCHOLES
113.0 VUH 
Chan 77

TRUAX
114.0 NGP 
Chan 87
N27°41.18'
W97°17.68'
L-20-21, H-7

YAWNS
N28°49.39'
W95°33.96'

TAKEOFF MINIMUMS:

- Rwys 13L/R, 31L/R, 35: Standard.
- Rwy 4: 300-1 or standard with minimum climb of 270' per NM to 300.
- Rwy 17: 300-1.
- Rwy 22: Standard with minimum climb of 290' per NM to 1500.

NOTE: For aircraft filed FL180 and above to Rio Grande Valley area or for aircraft filed FL180 and above overflying NGP VORTAC to international destinations.

NOTE: RADAR required.

SC-5, 12 OCT 2017 to 09 NOV 2017

SC-5, 12 OCT 2017 to 09 NOV 2017

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 4, 13L/13R, 22, 35: Climb on assigned heading for RADAR vectors to YAWNS INT, maintain 16000. Expect filed altitude 10 minutes after departure, thence. . .

TAKEOFF RWY 17: Climb heading 176° to 700 before turning, then climb on assigned heading for RADAR vectors to YAWNS INT, maintain 16000. Expect filed altitude 10 minutes after departure, thence....

TAKEOFF RWYS 31L/31R: Climb heading 311° to 800 before turning, then climb on assigned heading for RADAR vectors to YAWNS INT, maintain 16000. Expect filed altitude 10 minutes after departure, thence....

....on VUH R-228 and NGP R-047 to NGP VORTAC.

TRUAX SEVEN DEPARTURE