


SC-3, 04 JAN 2018 to 01 FEB 2018

**TOP ALTITUDE:
ASSIGNED BY ATC**

D-ATIS 124.4
CINC DEL 125.5 263.0
CPDLC
GND CON 121.9 348.6
AUSTIN TOWER 121.0 281.5
AUSTIN DEP CON 127.225 317.65

SAN ANGELO
SJT

FL180
293°
(9/1)




NOTE: RADAR required.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV-1.

AEROZ

AMUSE
5000

293°
(3/3)



TAKEOFF MINIMUMS
Rwys 17L/R: Standard.
Rwys 35L/R: Standard with minimum climb of 240' per NM to 2600.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 17L/R: Climb heading 175° or as assigned by ATC for RADAR vectors to cross AMUSE at or above 5000. Thence...
TAKEOFF RWYS 35L/R: Climb heading 355° or as assigned by ATC for RADAR vectors to cross AMUSE at or above 5000. Thence...
... on track 293° to AEROZ, then on SAN ANGELO TRANSITION. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.

SAN ANGELO TRANSITION (AEROZ1.SJT):

SC-3, 04 JAN 2018 to 01 FEB 2018