


SC-3, 01 FEB 2018 to 01 MAR 2018

**TOP ALTITUDE:  
ASSIGNED BY ATC**

D-ATIS  
124.4  
CINC DEL  
125.5 263.0  
CPDLC  
GND CON  
121.9 348.6  
AUSTIN TOWER  
121.0 281.5  
AUSTIN DEP CON  
119.0 317.65

SAN ANGELO  
SJT

FL180  
293°  
(9/1)




NOTE: RADAR required.  
NOTE: DME/DME/IRU or GPS required.  
NOTE: RNAV-1.

AEROZ

AMUSE  
5000

293°  
(3/3)



TAKEOFF MINIMUMS  
Rwys 17L/R: Standard.  
Rwys 35L/R: Standard with minimum climb of 240' per NM to 2600.

NOTE: Chart not to scale.

**DEPARTURE ROUTE DESCRIPTION**

TAKEOFF RWYS 17L/R: Climb heading 175° or as assigned by ATC for RADAR vectors to cross AMUSE at or above 5000. Thence....

TAKEOFF RWYS 35L/R: Climb heading 355° or as assigned by ATC for RADAR vectors to cross AMUSE at or above 5000. Thence....

... on track 293° to AEROZ, then on SAN ANGELO TRANSITION. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.

SAN ANGELO TRANSITION (AEROZ1.SJT):

SC-3, 01 FEB 2018 to 01 MAR 2018