WAAS CH 53415 W28B	APP CRS 284°	Rwy Idg 10275 / TDZE 13 / Apt Elev 13

RNAV (GPS) PRM RWY 28L (CLOSE PARALLEL)

SAN FRANCISCO INTL (SFO)

DME/DME RNP-0.3 NA. Simultaneous approach authorized with LDA PRM RWY 28R and RNAV (GPS) PRM X RWY 28R. Use of FD or AP required during simultaneous operations. Dual VHF comm required. See additional requirements on AAUP. For inop ALS, increase LNAV/VNAV all Cats visibility to 2 SM. Rwy 28L and 28R separated by 750 feet centerline to centerline. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 3°C (38°F) or above 54°C (130°F).

#RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4000 direct OLYMM and hold, continue climb-in-hold to 4000.

*Missed approach requires minimum climb of 300 feet per NM to 1500.

D-ATIS	NORCAL APP CON	SAN FRANCISCO TOWER	GND CON	CLNC DEL	CPDLC
113.7 115.8 118.85	134.5 338.2	120.5 269.1 PRM 125.15	121.8	118.2	





TDZ/CL Rwys 19L and 28R
REIL Rwys 1L, 1R and 10L
HIRL all Rwys



CATEGORY	A	B	C	D
LPV DA*#	213/24 200 (200-½)			
LPV DA	769-1¾ 756 (800-1¾)			
LNAV/VNAV DA	754-1¾ 741 (800-1¾)			

SW-2, 24 MAY 2018 to 21 JUN 2018
SW-2, 24 MAY 2018 to 21 JUN 2018