LOC I-BWI	APP CRS	Rwy ldg	5000
111.95	335°	TDZE	124
		Apt Elev	143

BALTIMORE/ WASHINGTON INTL THURGOOD MARSHALL (BWI)
ILS or LOC RWY 33R

DME required. DME from BAL VORTAC. Simultaneous reception of I-BWI and BAL DME required. Simultaneous approach authorized with Rwy 33L Inoperative table does not apply to S-IL 33R. For inoperative MALSR, increase S-LOC 33R visibility to RVR 5000. Helicopter visibility reduction below RVR 4000 NA.

MALSR

MISSED APPROACH: Climb to 3000 on heading 335° and BAL VORTAC R-337 to KRENE/ BAL 12.9 DME and hold.

D-ATIS	POTOMAC APP CON		BALTIMORE TOWER	GND CON	CLNC DEL
115.1 127.8	119.0 282.275 (020°-100°) 119.7 290.475 (131°-180°)		119.4 257.8	121.9	118.05
	124.55 317.425 (101°-130°) 128.7 307.9 (181°-019°)				

RADAR REQUIRED

ALTERNATE MISSED APCH FIX: WESTMINSTER EMI 117.9 Chan 126

CPDLC

KRENE BAL 12.9

LOCALIZER 111.95 I-BWI

EXEVE BAL 2.5 RADAR

ORIOL BAL 5.8 RADAR

BALTIMORE 115.1 BAL Chan 98

(IF) DUDDS BAL 12 RADAR

MSA BAL 25 NM: 2600, 2200

ELEV 143 D TDZE 124

TWR

10502 X 150

5000 X 100

7500 X 150

TDZ/CL Rwys 10 and 33L
REIL Rwys 15L and 33R
HIRL all Rwys

335° 5.8 NM from FAF

FAF to MAP 5.8 NM					
Knots	60	90	120	150	180
Min:Sec	5:48	3:52	2:54	2:19	1:56

3000 hdg 335°

BAL R-337 KRENE BAL 12.9

*LOC only.

*JST 1.3

EXEVE BAL 2.5 RADAR

ORIOL BAL 5.8 RADAR

DUDDS BAL 12 RADAR

335° 3000

2000

*940

GS 3.00° TCH 47

1.2 NM 1.3 NM 3.3 NM 6.3 NM

CATEGORY	A	B	C	D
S-ILS 33R	333/40	209 (200-¾)	NA	
S-LOC 33R	540/40	416 (400-¾)	NA	
C CIRCLING	640-1 497 (500-1)	660-1 517 (600-1)	NA	

NE-3, 24 MAY 2018 to 21 JUN 2018
NE-3, 24 MAY 2018 to 21 JUN 2018