LOC/DME I-GXZ	APP CRS	Rwy Idg	8800
110.1	275°	TDZE	990
Chan 38		Apt Elev	1026

ILS RWY 26R (SA CAT I & II)

HARTSFIELD-JACKSON ATLANTA INTL (ATL)

SA CAT I: Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH.
SA CAT II: Reduced lighting: Requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown.
Simultaneous approach authorized with Rwy 27R or 27L or 28, or Rwys 27R and 28.

MALSR

MISSED APPROACH: Climb to 1400 then climbing right turn to 3500 on ATL VORTAC R-005 to TROYS INT/ATL 15 DME and hold.

D-ATIS	ATLANTA	ATLANTA TOWER					ALL	GND CON			ALL
ARR 119.65	APP CON	8L-26R	8R-26L	9L-27R	9R-27L	10-28	RWYS	(8L-26R,8R-26L)	(9L-27R,9R-27L)	10-28	RWYS
DEP 125.55	127.9 379.9	119.1	125.325	123.85	119.3	119.5	254.4	121.9	121.75	121.65	254.4

CLNC DEL 118.1 | CPDLC

ALT MISSED APPROACH
PEACHTREE PDK 116.6 Chan 113
R-003 I-183° 003

TROYS ATL 15
005° 185°
115.4 RMG R-115 Chan 101
ATL R-005

PEACHTREE 116.6 PDK Chan 113

RADAR REQUIRED

2049 2049 2048 2049 2049 2049
R-186 R-166 R-153 R-138

LOCALIZER 110.1 I-GXZ Chan 38

AJAAY INT I-GXZ 6.9 RADAR

2049 (IAF) ZELOW INT I-GXZ 21.6 RADAR

1304 1179 1174 1290 1260

2700 4000 5000
275° 275° 275° 095°
(5) (3.8) (6)

ATLANTA 116.9 ATL Chan 116

BAMBU INT I-GXZ 11.9 RADAR
(IF) HAINZ INT I-GXZ 15.6 RADAR

MSA ATL 25 NM
3100

ELEV 1026 | D | TDZE 990

HIRL all Rwys
TDZ/CL Rwys 8L, 9R, 10, 26R, 27L and 28

1400 | 3500 ATL R-005 | TROYS

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 69).

AJAAY INT I-GXZ 6.9 RADAR
BAMBU INT I-GXZ 11.9 RADAR
HAINZ INT I-GXZ 15.6 RADAR
ZELOW INT I-GXZ 21.6 RADAR

2700 4000 5000 275° 5000
GS 3.00° TCH 55

1149' 5.2 NM 5 NM 3.8 NM 6 NM

CATEGORY	A	B	C	D
S-ILS 26R	SA CAT I	RA 170/14	150	DA 1140
S-ILS 26R	SA CAT II	RA 110/12	100	DA 1090

SA CATEGORY I & II ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

SE-4, 21 JUN 2018 to 19 JUL 2018